

DW-690 Ciechanowiec - Ostrożany (km 41+650)

km skrzyżowani a	strona drogi	średnia szerokość	długość	warstwy bitumiczne średniej grub. 10 cm	bruk granitowy 16 - 20 cm	kruszywo kamienne średniej grubości 10 cm	kruszywo kamienne średniej grubości 15 cm
		m	m	m2	m2	m2	m2
23+880,00	L	gruntowa					
24+587,97	P	gruntowa					-
25+383,09	P	3,0	16	-	-	-	65
26+005,36	P	gruntowa					
26+101,71	L	3,0	7	-	-	-	46
27+637,09	L	6,0	40	444	466	490	
27+819,60	L	gruntowa					
27+827,00	P	3,7	23	-	-	-	107
28+220,44	L	2,7	15	-	-	-	87
29+193,45	L	gruntowa					
29+205,18	P	gruntowa					
30+228,00	P	gruntowa					
31+130,10	P	5,0	33	185	194	204	
31+130,78	L	gruntowa					
31+904,33	P	5,0	15	95	100	105	
33+965,78	L	5,0	59	320	336	353	
33+965,78	P	5,0	63	345	362	380	
34+413,33	L	gruntowa					
34+921,86	L	gruntowa					
35+127,13	P	gruntowa					
36+869,29	P	gruntowa					
36+872,04	L	gruntowa					
37+299,04	P	3,5	38		152		
37+572,62	P	5,5	35	230	241	253	
37+573,70	L	4,0	23	112	118	123	
38+093,75	L	gruntowa					
38+248,16	P	5,0	32	170	179	187	
38+528,22	P	gruntowa					
39+215,14	L	gruntowa					
39+215,14	P	gruntowa					
40+246,95	P	7,0	12	-	-	-	94
40+247,33	L	gruntowa					
41+095,85	L	gruntowa					
41+096,45	P	3,8	24	98	103	108	
41+474,00	P	gruntowa					
41+438,61	-(wyjazd)			215	226	237	
41+503,46	L-(wyjazd)			200	210	221	
RAZEM			435	2 414	2 686	2 661	399
Razem [Mg]				579	967	426	96

- frezowanie istniejącej w-wy ścieralnej na skrzyżowaniach o nawierzchni bitumicznej:

km skrzyżowani	strona drogi	Lokalizacja		grubość 4 cm [Mg]	grubość 5 cm [Mg]
		km -od	km-do		
27+637,09	L	0+043,62	0+048,62		2,9
31+130,10	P	0+035,00	0+040,00	2,4	
31+904,33	P	0+016,80	0+021,80	2,4	
33+965,78	L	0+060,68	0+065,68		3,0
33+965,78	P	0+067,50	0+072,50		2,4
37+572,62	P	0+028,60	0+033,60		4,1
37+573,70	L	0+035,82	0+040,82		3,2
38+248,16	P	0+035,00	0+040,00	2,4	
41+096,45	P	0+025,00	0+030,00	1,8	
razem [Mg]				9,0	15,7
ogółem [Mg]				24,7	
m2				275,0	275,0