

**UZIARNIENIE MIESZANKI MINERALNEJ**  
**DROGA NR 653 Olecko - Bakalarzewo - Suwałki m.PRZEBRÓD**  
**WARSTWA II**

lokalizacja km+hm	sito																
	0,075	0,150	0,180	0,300	0,420	0,800	2,000	4,000	6,300	8,000	10,000	12,000	16,000	20,000	25,000	31,500	38,100
23+650 L	5,1	6,9	8,1	14,1	18,9	35,3	48,6	58,5	66,6	73,2	82,2	87,6	100,0	100,0	100,0	100,0	100,0
23+800 P	6,4	7,8	8,6	14,4	20,2	41,0	56,3	67,9	75,7	81,5	91,3	94,5	96,8	100,0	100,0	100,0	100,0
24+350 L	8,3	10,5	12,1	17,9	22,1	40,9	55,3	67,5	77,0	85,5	89,7	100,0	100,0	100,0	100,0	100,0	100,0
24+850 P	5,5	7,9	9,1	16,3	22,3	43,8	62,3	75,1	84,4	89,5	94,3	100,0	100,0	100,0	100,0	100,0	100,0
średnia	6,3	8,3	9,5	15,7	20,9	40,3	55,6	67,3	75,9	82,4	89,4	95,5	99,2	100,0	100,0	100,0	100,0
granica dolna w. wiążąca 0/16	5,0	6,0	7,0	10,0	13,0	20,0	30,0	42,0	54,0	60,0	67,0	77,0	87,0	100,0	100,0	100,0	100,0
granica górna w. wiążąca 0/16	8,0	14,0	16,0	21,0	25,0	33,0	45,0	60,0	73,0	83,0	89,0	100,0	100,0	100,0	100,0	100,0	100,0
granica dolna podbudowa 0/25	4,0	5,0	5,0	6,0	7,0	12,0	19,0	27,0	36,0	42,0	48,0	57,0	66,0	76,0	87,0	100,0	100,0
granica górna podbudowa 0/25	7,0	11,0	12,0	15,0	18,0	24,0	35,0	47,0	58,0	65,0	71,0	81,0	90,0	100,0	100,0	100,0	100,0

**Krzywe uziarnienia mieszanki mineralnej dla poszczególnych próbek na tle  
krzywych granicznych jak dla warstwy wiążącej 0/16 mm i warstwy  
podbudowy 0/25mm KR 3-6 wg normy PN-S-96025;2000**

